



OPC		5	10	20
Rated Torque [in-lbs / N-m]		4.4 / 0.5	8.9 / 1	18 / 2
Coil (20°C)	Voltage [DC-V]	24		
	Current [A]	0.48	0.58	0.75
	Resistance [Ω]	50	41	32
	Wattage [W]	12	14	18
	Time Constant [ms]	11	15	18
Drag Torque (reference) [in-lbs]		0.089	0.18	0.35
Max Slip Wattage [W]		15	25	45
Max Allowable Speed [rpm]		1800	1800	1800
Moment of Inertia (J) [kg-cm <sup>2</sup> ]	Input	0.153	0.258	0.838
	Output	0.014	0.018	0.07
Shaft [mm]	dh7	5	7	12
	t	4.5	6.5	11.5
Dimensions [mm]	A1h8	50	54	69
	A2	50	54	69
	B	70	76	92
	Ch7	40	42	54
	E	30	34	46
	F	60	66	82
	G	4.5	4.5	4.5
	H	3xM4	3xM4	4xM4
	L	77	83	116
	M	25	27	47
	N	4	4	4
	P	11	13	25
	Q	5	5	6
	R	8.5	8.5	15
	S	25.5	18	22
T	13.5	15.5	33	
U	10.5	12.2	24	
Y	9	10	20	
Weight [lbs / kg]		1.5 / 0.7	1.8 / 0.8	2.9 / 1.3

[ 1" = 25.4mm ]